



# TECHNICAL CARD

Ref. Reg.165  
Review: 1  
Date: 06/01/2015

## AHM 2500 LSL

TECHNICAL SPECIFICATIONS		INTERNAL DIMENSIONS	
MODEL	AHM 2500 LSL	Height	615 mm
EQUIPMENT TYPE	Freezer	Depth	720 mm
		Width	2360 mm
INNER TEMPERATURE RANGE	-24 °C / -16 °C -11,2 °F / 3,2 °F	INFO	
GROSS VOLUME	938 l   33,13 Ft <sup>3</sup>	Lid/door Type	Lid - Glass
NET VOLUME	886 l   31,29 Ft <sup>3</sup>	External coating	Pre Painted Sheet
EXTERNAL DIMENSIONS		Internal coating	Pre Painted Sheet
Height	840 mm	Wall Thickness	70 mm
Depth	880 mm	Climate Class	4
Width	2500 mm	Freezing Capacity	N/A



Imagem Indisponível  
Imagem No Disponible  
Unavailable Image

ENERGETIC FEATURES	
VOLTAGE / FREQUENCY	230V - 50Hz
NOMINAL CURRENT	2,93 A
POWER	380 W
CONSUMPTION	8,5 kWh/24hr
ENERGY EFFICIENCY	-
COMPRESSOR PROTECTION	External – Bimetallic
NOISE LEVEL	<55 dB
ACCESSORIES	
BASKETS	0
DIVIDER	4
SHELVES	0
WATER DRAIN	Yes
WATER TRAY	Yes
THERMOMETER	Yes - Digital
LOCK	No

COMPONENTS	
COMPRESSOR	Embraco
Modelo	NT2168U
Displacement	16,8 cm <sup>3</sup>
Rated Power	516 W
CONDENSER	Ventilated
VENTILATORS	EBMPAPST
Power	10 W
THERMOSTAT	Digital
REFRIGERANT	R290
Quantity	150 g   5,29 oz
Operating Pressure	300 Psi
EVAPORATOR	Hidden
LIGHT	LED
Power	16 W

Approved by:  
Date: 12/01/2016  
Document uncontrolled when printed or copied.

This leaflet is merely informative and subject to changes in technical data, and may not be used as a contractual document.

©All Rights Reserved



# TECHNICAL CARD

Ref. Reg.165

Review: 1

Date: 06/01/2015

## AHM 2500 LSL AD

TECHNICAL SPECIFICATIONS	
MODEL	AHM 2500 LSL AD
EQUIPMENT TYPE	Freezer - Automatic Defrost
INNER TEMPERATURE RANGE	-24 °C / -16 °C -11,2 °F / 3,2 °F
GROSS VOLUME	938 l   33,13 Ft <sup>3</sup>
NET VOLUME	886 l   31,29 Ft <sup>3</sup>
EXTERNAL DIMENSIONS	
Height	840 mm
Depth	880 mm
Width	2500 mm

INTERNAL DIMENSIONS	
Height	615 mm
Depth	720 mm
Width	2360 mm
INFO	
Lid/door Type	Lid - Glass
External coating	Pre Painted Sheet
Internal coating	Pre Painted Sheet
Wall Thickness	70 mm
Climate Class	4
Freezing Capacity	N/A



Imagem Indisponível  
Imagem No Disponible  
Unavailable Image

ENERGETIC FEATURES	
VOLTAGE / FREQUENCY	230V - 50Hz
NOMINAL CURRENT	2,93 A
POWER	400 W
CONSUMPTION	9,1 kWh/24hr
ENERGY EFFICIENCY	-
COMPRESSOR PROTECTION	External - Bimetallic
NOISE LEVEL	<55 dB
ACCESSORIES	
BASKETS	0
DIVIDER	4
SHELVES	0
WATER DRAIN	Yes
WATER TRAY	Yes
THERMOMETER	Yes - Digital
LOCK	No

COMPONENTS	
COMPRESSOR	Embraco
Modelo	NT2168U
Displacement	16,8 cm <sup>3</sup>
Rated Power	516 W
CONDENSER	Ventilated
VENTILATORS	EBMPAPST
Power	10 W
THERMOSTAT	Digital
REFRIGERANT	R290
Quantity	150 g   5,29 oz
Operating Pressure	300 Psi
EVAPORATOR	Hidden
LIGHT	LED
Power	16 W

Approved by:

Date: 12/01/2016

Document uncontrolled when printed or copied.

This leaflet is merely informative and subject to changes in technical data, and may not be used as a contractual document.

©All Rights Reserved



# TECHNICAL CARD

## AHM 2500 LSL ADVS

Ref. Reg.165  
Review: 1  
Date: 06/01/2015

TECHNICAL SPECIFICATIONS		INTERNAL DIMENSIONS	
MODEL	AHM 2500 LSL ADVS	Height	615 mm
EQUIPMENT TYPE	Freezer - Automatic Defrost Variable Speed	Depth	720 mm
		Width	2360 mm
INNER TEMPERATURE RANGE	-24 °C / -16 °C -11,2 °F / 3,2 °F	INFO	
GROSS VOLUME	938 l   33,13 Ft <sup>3</sup>	Lid/door Type	Lid - Glass
NET VOLUME	886 l   31,29 Ft <sup>3</sup>	External coating	Pre Painted Sheet
EXTERNAL DIMENSIONS		Internal coating	Pre Painted Sheet
Height	840 mm	Wall Thickness	70 mm
Depth	880 mm	Climate Class	4
Width	2500 mm	Freezing Capacity	N/A



Imagem Indisponível  
Imagen No Disponible  
Unavailable Image

ENERGETIC FEATURES	
VOLTAGE / FREQUENCY	220/230V - 50/60Hz
NOMINAL CURRENT	2,01 A
POWER	430 W
CONSUMPTION	8 kWh/24hr
ENERGY EFFICIENCY	-
COMPRESSOR PROTECTION	External – Bimetallic
NOISE LEVEL	<55 dB
ACCESSORIES	
BASKETS	0
DIVIDER	4
SHELVES	0
WATER DRAIN	Yes
WATER TRAY	Yes
THERMOMETER	Yes - Digital
LOCK	No

COMPONENTS	
COMPRESSOR	Danfoss
Modelo	SLV15CNX.2
Displacement	15,28 cm <sup>3</sup>
Rated Power	607 W
CONDENSER	Ventilated
VENTILATORS	EBMPAPST
Power	10 W
THERMOSTAT	Digital
REFRIGERANT	R290
Quantity	150 g   5,29 oz
Operating Pressure	300 Psi
EVAPORATOR	Hidden
LIGHT	LED
Power	16 W

Approved by:  
Date: 12/01/2016  
Document uncontrolled when printed or copied.

This leaflet is merely informative and subject to changes in technical data, and may not be used as a contractual document.

©All Rights Reserved



# TECHNICAL CARD

Ref. Reg.165  
Review: 1  
Date: 06/01/2015

## AHM 2500 LSL VCC

TECHNICAL SPECIFICATIONS		INTERNAL DIMENSIONS	
MODEL	AHM 2500 LSL VCC	Height	615 mm
EQUIPMENT TYPE	Freezer - Automatic Defrost Variable Speed	Depth	720 mm
		Width	2360 mm
INNER TEMPERATURE RANGE	-24 °C / -16 °C -11,2 °F / 3,2 °F	INFO	
GROSS VOLUME	938 l   33,13 Ft <sup>3</sup>	Lid/door Type	Lid - Glass
NET VOLUME	886 l   31,29 Ft <sup>3</sup>	External coating	Pre Painted Sheet
EXTERNAL DIMENSIONS		Internal coating	Pre Painted Sheet
Height	840 mm	Wall Thickness	70 mm
Depth	880 mm	Climate Class	4
Width	2500 mm	Freezing Capacity	N/A



Imagem Indisponível  
Imagen No Disponible  
Unavailable Image

ENERGETIC FEATURES	
VOLTAGE / FREQUENCY	220/230V - 50/60Hz
NOMINAL CURRENT	3,54 A
POWER	370 W
CONSUMPTION	6,6 kWh/24hr
ENERGY EFFICIENCY	-
COMPRESSOR PROTECTION	External – Bimetallic
NOISE LEVEL	<55 dB
ACCESSORIES	
BASKETS	0
DIVIDER	4
SHELVES	0
WATER DRAIN	Yes
WATER TRAY	Yes
THERMOMETER	Yes - Digital
LOCK	No

COMPONENTS	
COMPRESSOR	Embraco
Modelo	VNEK213U
Displacement	13,54 cm <sup>3</sup>
Rated Power	670 W
CONDENSER	Ventilated
VENTILATORS	EBMPAPST
Power	10 W
THERMOSTAT	Digital
REFRIGERANT	R290
Quantity	150 g   5,29 oz
Operating Pressure	300 Psi
EVAPORATOR	Hidden
LIGHT	LED
Power	16 W

Approved by:  
Date: 12/01/2016  
Document uncontrolled when printed or copied.

This leaflet is merely informative and subject to changes in technical data, and may not be used as a contractual document.

©All Rights Reserved